

Grand Strand Quilters

Narrow Brick Road 53" x 69"

Original pattern by Rachael McDaniels Hayes

Kit Supplies:

- 43 assorted bricks @ 4 ½" x 8 ½" (BR units)
- 10 assorted bricks @ 4 ½" x 4 ½" (HBR units)
- 20 background bricks @ 4 ½" x 8 ½" (WBR units)
- 4 background bricks @ 4 ½" x 4 ½" (HW units)
- 5 - 2 ½" WOF strips – INNER BORDER 1
- 6 - 5" WOF strips – OUTER BORDER 2

(WOF = Width Of Fabric)

INSTRUCTIONS: *Please read through ALL instructions, including back page, before beginning.*

Your first row will consist of two assorted bricks units (BR)(BR), one background brick (WBR) then two more assorted brick units (BR)(BR). Each successive row will move one half brick to the left. Row two will start with a Half Brick unit (HBR), then a whole brick (BR), a background brick (WBR), then two whole bricks (BR)(BR), then a half brick (HBR). Keep shifting rows to the left. Detailed row instructions are given below. Label each row to make the final quilt assembly easier.

ROW 1, ROW 7 & ROW 13 = BR, BR, WBR, BR, BR

ROW 2, ROW 8 = HBR, BR, WBR, BR, BR, HW

ROW 3, ROW 9 = BR, WBR, BR, BR, WBR

ROW 4, ROW 10 = HBR, HBR, BR, BR, WBR, HBR

ROW 5, ROW 11 = WBR, BR, BR, WBR, BR

ROW 6, ROW 12 = HW, BR, BR, WBR, BR, HBR

ROW 14 = HBR, BR, WBR, BR, BR, HBR

Once your rows are constructed, layout your quilt to check the design. Sew Row 1 to Row 2, Row 3 to Row 4, etc. Continue combining rows. Once all rows are joined together, square up the top. Add inner border then outer border.

Paved with Bricks 50" x 65"

Supplies:

- 81 assorted bricks @ 3 ½" x 6 ½" (FULL sized Bricks)
- 18 assorted bricks @ 3 ½" x 3 ½" (HALF sized Bricks)
- 5 - 1 ½" WOF strips – INNER BORDER 1
- 6 - 5" WOF strips – OUTER BORDER 2

Odd numbered rows (1, 3, ..., 17) have seven full size bricks

Even number rows (2, 4, ..., 18) have one half size brick, 6 full size bricks, then one half size brick.

NARROW BRICK ROAD



GENERAL QUILTING DIRECTIONS AND HELPFUL HINTS:

- All seams are $\frac{1}{4}$ inch unless directions specify differently
- For best results, layout the rows of bricks and snap a picture. This will insure that the top goes together as designed.
- Stitch the rows of bricks together and press the seams in either direction. Pressing very important! Please do not skip this step
- If you have sewn the rows together accurately, each row should measure $40\frac{1}{2}$ ". Sew the rows together and square up the top before adding the borders. Again, this is very important to insure the top comes out square.

BORDERS

- Always measure the quilt top in 3 places before cutting borders. Top, Middle and Bottom, use the average of the three measurements to cut border lengths. Pin the borders to the two side of the quilt top and "ease" in any fullness and sew. Press seams toward the border strip. Repeat this process for the Top and Bottom of the quilt MEASURE FIRST, cut, pin, sew and press. Repeat for the outer border.
- Once the top is complete, give it a final pressing. Check the back of the quilt ... are all the seams going in the right direction and are they neatly pressed?
- Measure the top and write your name along with the measurements on a slip of paper and pin it to the top.

Questions??? Contact Margo Woolard at 843-655-4826. Thank You! Your help is greatly Appreciated!